

Additional Industrial Products

Crosby Terminator™ Wedge Socket (P-00146-1)



- Basket is cast steel
- Individually magnetic particle inspected
- Pin diameter and jaw opening allow wedge and socket to be used in conjunction with open swage and spelter sockets.
- Secures the tail or 'dead end' of the wire rope to the wedge, thus eliminating loss or 'punch out' of the wedge
- Eliminates the need for an extra piece of rope and is easily installed
- Eliminates the potential breaking off of the tail due to fatigue
- The tail, which is secured by the base of the clip and the wedge, is left undeformed and available for reuse.
- Incorporates Crosby's patented Quic-Check® "Go" and "No-Go" feature cast into the wedge. The proper size rope is determined when the following criteria are met:
 1. The wire rope should pass through the "Go" hole in the wedge.
 2. The wire rope should NOT pass through the "No Go" hole in the wedge.
- Utilizes standard Crosby Red-U-Bolt wire rope clip
- Generates a minimum efficiency of 80% based on the catalog breaking strength of the wire rope
- Standard wedge socket can be retrofitted with the new style Terminator wedge.
- Available with Bolt, Nut and Cotter Pin

Wire Rope		S-421T Stock No. Complete Assembly	S-421T Weight Each		S-421 TW Stock No. Wedge Only	S-421 TW Weight Each	
in.	mm		lbs.	kg.		lbs.	kg.
3/8	10	1035000	3.2	1.4	1035555	0.5	0.2
1/2	13	1035009	6.2	2.8	1035564	1.1	0.5
5/8	16	1035018	9.7	4.4	1035573	1.8	0.8
3/4	19	1035027	14.5	6.6	1035582	2.6	1.2
7/8	22	1035036	21.5	9.8	1035591	4	1.8
1	25	1035045	30.8	13.9	1035600	5.4	2.4
1 1/8	29	1035054	45.3	20.5	1035609	7.8	3.6
** 1 1/4	32	1040448	57.5	26.1	1040607	6.8	3.1

** 1 1/4 in (32 mm) not available in Terminator™ style

For more information, call: 1-877-774-3370