


# Accessories

Part Number	Description	Used With:	Specifications
233740	Fist Grip 5/16 in. (8 mm)	Beams, parapet and cornice hooks/clamps, 700525-1 and 4963-XX	Designed for attaching safety tieback lines, but not recommended for use on the suspension wire rope
233745	Fist Grip 3/8 in. (10 mm)	Beams, parapet and cornice hooks/clamps, 700525-1 and Spider Modular Platforms	Designed for attaching safety tieback lines, but not recommended for use on the suspension wire rope
557026	5/8 in. (16 mm) Bolt Type Anchor Shackle	Rigging	Attaches the suspension wire rope eye to the rigging device when the rigging device does not provide for ready attachment
A-11835	Caster; 12 in. (305 mm)	For rolling towers	1 3/8 in. (35 mm) stem; max. load 1,200 lbs. (545 kg)
A-11934	Caster 8 in. (20 mm)	For rolling towers	1 3/8 in. (35 mm) stem; max. load 750 lbs. (341 kg)



## BD-00019

Designed for a variety of applications, including:

- Anchoring scaffolding to secure structures
- Material handling and lifting
- Demolition

A 2,000 lb. (907.2 kg) maximum safe working load is established by drilling a 1 in. (25 mm) diameter hole in cured concrete and inserting the Spider anchor.

*This unit is NOT designed for fall protection use. See models BD-00009 and BD-00018 for fall protection applications.*

More information online at  
[www.spiderstaging.com](http://www.spiderstaging.com)

For more information, call: 1-877-774-3370