

Safety Line



The 704076 is a combination fiber rope with excellent wear and high strength to weight. The balanced rope construction offers the durability of polyester ropes and higher strengths than those of other combination ropes.

The 704076-xxx meets or exceeds the requirements of OSHA 1926 Subpart M and ANSI A10.14 at the time of shipment. This safety line is also ANSI Z359.1-2007 compliant.

Specifications:	704076-xxx
Weight:	9.4 lbs. per 100 ft (4.3 kg per 30.5 m)
Minimum Tenacity/Elongation:	5,600 lbs. (2,540.1 kg)
Tested Tenacity:	Exceeds 10,000 lbs. (4,535.9 kg)
Composition:	680K Denier Industrial Polyester/680K Denier High Tenacity Copolymer over internal red & black tracers
Identification:	Red and Black Internal Tracer

For lifelines by the reel, see page 229. For finished lifeline assemblies, see below.



Termination Plates (P-00245)

Eliminate knots in your lifeline. Knots can reduce lifeline strength by as much as 50% or more, depending on the type of knot. Rated capacity: 5,000 lbs. (2,268 kg)

Safety Rope with Eye Splice Terminations

Part Number	Description
P-00250-50	LIFELINE; 50 ft (15.2 m); SNAPHOOK
P-00250-100	LIFELINE; 100 ft (30.5 m); SNAPHOOK
P-00250-150	LIFELINE; 150 ft (45.7 m); SNAPHOOK
P-00250-200	LIFELINE; 200 ft (61 m); SNAPHOOK
P-00250-250	LIFELINE; 250 ft (76.2 m); SNAPHOOK
P-00250-600	LIFELINE; 600 ft (182.9 m); SNAPHOOK
P-00261-100	LIFELINE; 100 ft (30.5 m); THIMBLE ONLY
P-00261-150	LIFELINE; 150 ft (45.7 m); THIMBLE ONLY
P-00261-200	LIFELINE; 200 ft (61m); THIMBLE ONLY
P-00261-250	LIFELINE; 250 ft (76.2 m); THIMBLE ONLY
P-00261-300	LIFELINE; 300 ft (91.4 m); THIMBLE ONLY
P-00261-400	LIFELINE; 400 ft (121.9 m); THIMBLE ONLY

More information online at
www.spiderstaging.com

For more information, call: 1-877-774-3370